

Cleaning Nelplas® Protective Wallcovering

| PROBLEM | STAINING AGENT | SOLUTION |
|--|--|---|
| Discoloration at seams and edges of sheets. | Dried adhesive or caulking residue from installation of protective wallcovering. | Use mineral spirits, naphtha, or other commercially available solvent. Apply sparingly with a clean rag and rub in a small circular manner, being careful not to spread the adhesive over a larger area. The reactivated adhesive or caulking will be suspended in the solvent. The entire stained area should be rinsed with clean water before the solvent evaporates. |
| Residue from general pedestrian traffic. | Oils, soda, juice, coffee, mustard, food stains, etc. | Use a commercially available liquid cleanser (SoftScrub®, Fantastik®, 409®, etc.) that does not include bleach or ammonia. Apply product sparingly and wipe in small circles with clean, damp rag. |
| Tough stains embedded in texture of sheet. | Grease, ink, blood, betadine, etc. Permanent marker, paint, nail polish, etc. | Use a commercially available liquid cleanser (SoftScrub®, Fantastik®, 409®, etc.) that does not include bleach or ammonia. Apply product sparingly and scrub in small circles with a stiff nylon bristle brush. Rinse the area with clean water. Repeated treatment may be required for especially tough stains. Use a commercially available graffiti remover*. These are specialized spot cleaners that should be used for stained areas only. A stiff nylon short bristle brush may be necessary to remove some stains from the textured surface of the sheet. These cleaners should be rinsed thoroughly with clean water. |
| Scuff marks and black streaks on texture of sheet. | Rubber transfer from carts, gurneys, wheel-chairs, heel marks, etc. | Use a stiff nylon short bristle brush with a mild soap and water solution. Repeated scrubbing may be required to remove rubber that has transferred to the textured surface of the sheet. |
| Dull appearance or haze. | Residue from cleaning agents not properly rinsed from wallcovering. | Use special cleaners such as Johnson Wax Step-Off and a stiff nylon short bristle brush. These cleaners should be rinsed thoroughly with clean water. |

***Sources for graffiti removers:**

"Crown Anti-Vandal Spray" by Aervoe Industries
 "DWR-II" by Chemique, Inc.
 "Write Away" by Zep

800-227-0196
 (609) 225-4161
 877-428-9937

DO NOT USE THE FOLLOWING PRODUCTS:

Powdered cleansers (Ajax®, Comet®, Spic and Span®, etc.)
 Ammonia based cleansers (Mr. Clean®, Top Job®, etc.)
 Acrylic floor strippers
 Undiluted bleach

WHY NOT?

Leaves a chalky residue.
 Leaves a hazy film.
 Permanently discolors surface.
 Leaves a hazy film.

The suggestions and data in this document are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.

NELPLAS®
 Wall Protection Systems

800-628-0449 • www.nelplas.com • Division 10 26 00